



Cobra D500 Drophammer Rig

Tight access mini drophammer rig

Key Features

- ★ Restricted Access
- ★ Low Headroom
- ★ Fit through a doorway

Technical Specifications

Engine: Kubota 3 Cyl D1105 18.5 kw @ 3000 rpm

Controls: Onboard Controller

Maximum Diameter Holes: 273 mm

Casings: 273 mm

Drophammer Guide

Emission Sound Pressure: 77.1 dB

Sound Power Level: 85.1 dB



Dimensions

Length: 2908 mm

Minimum Width: 810 mm

Maximum Width: 1656 mm

Maximum Height: 4256 mm

Basic Weight: 1650 kg

Transport Length: 3172 mm

Transport Width: 788 mm

Transport Height: 1877 mm



Telescopic Mast

Hydraulic Mast Tilt: 10°

Hydraulic Mast Extension: 1000 mm

Winch: Pullmaster PL 5

Winch Capacity: Up to 750 KG

Ground Bearing Pressure

Hydraulic Legs: 312 N/m²

Driving: 46 N/m²

Angle Of Forward Inclination: 20°

Angle Of Side Tilt: 15°

Hinowa PT 15 Undercarriage

Tracks: Rubber / Adjustable

Max Speed: 2.2 km/h

Hydraulic Pumps

1: 17 ccm @ 50 l/min, 200 Bar

2: 4 ccm @ 12 l/min, 200 Bar

B25 Machine Base

2 Front / 2 Back Hydraulic Stabilisers: Turn-able

Stabiliser Enlargement: 200 mm

